


Product data Sheet

US Walnut Sanded White Oil



Product Details

Product Code	NSSESKW
Product Collection	Select
Construction	Solid 3 layered engineered
Species	US Walnut
Grade	Character
Pattern	Plank
Vulcano	NOT
Finish	White oil
Surface	Sanded
Profile	tongue & groove
Edge Profile	micro bevel
Top layer	4.5mm
Middle layer	Spruce
Back layer	4.5mm
Adhesive	PVA Manufacture with water, carbon, lime & acetic acid
Thickness	16mm or 19mm
Widths	135mm - 240mm
Lengths	1200mm - 2400mm
Wide Plank	N/A
Maintainance	Visit www.mafi.com.au/maintainance
Residential Warranty	25 year structure warranty
Commercial Warranty	5 year warranty

Installation Methods

Fully Bonded	Yes (recommended)
Nailed	Brad Nail Through Tongue
Floated on Underlay	Yes (PVA Tongue & Groove)
Over Joist	19mm only @ 400mm centres
Over Underfloor Heating	Yes (see below)

Mafi Natural Wooden Floors are suitable for use over under floor heating systems. Please have a look into the Mafi guide for installing over underfloor heating. With a room temperature of 21 °C the floor's surface temperature should be a maximum of 29 °C and should not exceed this temperature. Please refer to Mafi installation over underfloor heating guide for full instructions.

Grading Criteria

Branches	healthy knots are permitted. putty filled knots are permitted up to 15mm.
Cracks	cracks are not permitted
Cotter	permitted
Worn	not permitted
Discolourisation	permitted
Grain	permitted
Sorting Picture	N/A
Color Difference	is a characteristic of natural wood


Technical Criteria

Origin	Austria
Responsible Certification	Living Product Challenge, Declare Label red list free, FSC, MAS green certificate, 0 waste solution
Janka Hardness Rating	42-48 N/mm ²
Formaldehyde Emission	E1
Pentachlorophenol Emission	< 5 ppm
Slip Testing	R11 P3
European fire classification	CFL-s1
Reaction to fire Floors (CRF)	3.6 kW/m ²
Reaction to fire Walls & Ceilings	Group 3
Thermal Resistance	0,08 - 0,19 m ² *K/W

mafi

US Walnut Sanded White Oil

References



Dark walnut colour with slightly darker shades possible. Walnut plank in 3-layer construction with small bevel on long side and approx. 4 mm top layer, with approx. 4 mm backing in the same wood and middle layer conifer.

Tongue and groove on all sides for easy installation. Sapwood possible, healthy knots, also repairs up to max. 15 mm diameter and spot fillings are permitted.



US Walnut Sanded White Oil

mafi stands for sustainable and natural wooden floors

At the core of mafi's philosophy is direct human contact with the natural material wood, because this contact has a positive effect on all our senses, whether we're at home, at work, or in a restaurant.

Our manufacturing process focuses on finishing the surfaces with natural oils and then drying them naturally in fresh air. The self-regenerative and antibacterial effects of the wood are also preserved.

mafi therefore stands for wood instead of plastic, for natural colour instead of artificial stained or painted colour, and for unique quality instead of interchangeability.

mafi wood floors are made with only natural elements and have no toxins, whereas artificial products can potentially be unhealthy, especially after long time periods.

Therefore, a "wood floor" becomes a plastic floor supported by wood. There is no known physical health benefit to a plastic coated wood floor whereas a wood floor that is natural has multiple health benefits.

Installations

Mafi floors should be installed by an experienced floor installer or competent carpenter. Please find mafi installation guide here www.mafi.com.au/installation/

If unsure on how to best install please contact one of our timber floor consultants to get assistance on selecting the best installation method.

Moisture content of the wood

The moisture content of mafi natural wooden floors is between 6 – 8 % ex works. (exception: all Vulcano floors are between 2 – 5 %). This is guaranteed through special analysers which are continuously calibrated.

Usage

All mafi natural wood floors comply with CE directives in accordance with ÖNORM EN 14342.

Due diligence

The subsurface as well as the goods for installation has to be checked if the standards are kept to the following:

Parquet works DIN 18356;

Wooden floors: DIN EN 13489;

Tolerances in building construction DIN 18202

Each plank or panel has to be checked regarding proper quality prior to installation.

The completion of a heating protocol is imperative if an installation on underfloor heating is realized.